



RODAMIENTOS RIGIDOS DE BOLA EN PULGADAS

Dimensiones							Capacidad de Carga		Velocidad Límite	Peso	Código Rodamiento
d		D		B		f's min	Dinámica	Estática	rpm	(Kg.)	
Pulg.	mm	Pulg.	mm	Pulg.	mm	Pulg.					
1/2	12.700	1-5/16	33.338	3/8	9.525	1/32	520	380	24000	0.03	RLS4
5/8	15.875	1-9/16	39.688	7/16	11.112	1/32	720	430	21000	0.06	RLS5
3/4	19.050	1-7/8	47.625	9/16	14.288	1/16	1000	630	17000	0.11	RLS6
7/8	22.225	2	50.800	9/16	14.288	1/16	1200	760	16000	0.13	RLS7
1	25.400	2-1/4	57.150	5/8	15.875	1/16	1400	970	14000	0.17	RLS8
1-1/8	28.575	2-1/2	63.500	5/8	15.875	1/16	1530	1020	12500	0.21	RLS9
1-1/4	31.750	2-3/4	69.850	11/16	17.462	1/16	1830	1230	11500	0.28	RLS10
1-3/8	34.925	3	76.200	11/16	17.472	1/16	2010	1390	10500	0.37	RLS11
1-1/2	38.100	3-1/4	82.550	3/4	19.050	1/32	2400	1700	9500	0.43	RLS12

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua
 Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com



BEARINGS & SEALS
 Rif. J-31541906-8 / Nit: 0551106039