



RODAMIENTOS DE CONTACTO ANGULAR (una hilera)

Dimensiones (mm)					Capacidad de Carga		Velocidad Límite (rpm)		Peso	Código Rodamiento
d	D	B	rs	r1s	Cr	Cor	Grasa	Aceite	(kg)	
60	110	22	1.5	1	61.5	49.0	6,600	8,800	0.765	7212
	130	31	2.1	1.1	98.0	71.5	5,900	7,900	1.74	7312
65	120	23	1.5	1	70.5	58.0	6,100	8,100	0.962	7213
	140	33	2.1	1.1	111	82.0	5,500	7,300	2.11	7313
70	125	24	1.5	1	76.5	63.5	5,700	7,600	1.09	7214
	150	35	2.1	1.1	125	93.5	5,100	6,800	2.56	7314
75	130	25	1.5	1	79.0	68.5	5,300	7,100	1.17	7215
	160	37	2.1	1.1	136	106	4,800	6,300	3.07	7315
80	140	26	2	1	89.0	76.0	5,000	6,600	1.39	7216
	170	39	2.1	1.1	147	119	4,500	5,900	3.65	7316
85	150	28	2	1	99.5	88.5	4,700	6,200	1.78	7217
	180	41	3	1.1	159	133	4,200	5,600	4.34	7317
90	160	30	2.0	1	118	103	4,400	5,900	2.18	7218
	190	43	3.0	1.1	171	147	4,000	5,300	5.06	7318

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua
 Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com