



## RODAMIENTOS AXIALES DE BOLAS

Dimensiones (mm)			Capacidad de Carga (kN)		Velocidad Límite (rpm)		Peso	Código Rodamiento
d	D	B	Cr	Cor	Grasa	Aceite	(kg)	
10	24	9	10	14	6500	10000	0.02	51100
	26	11	12.7	17.1	5700	8800	0.03	51200
12	26	9	10.3	15.4	6500	10000	0.022	51101
	28	11	13.2	19	5400	8300	0.034	51201
15	28	9	10.5	16.8	6100	9400	0.024	51102
	32	12	16.6	24.8	4900	7500	0.046	51202
17	30	9	10.5	18.2	6100	9400	0.028	51103
	35	12	17.2	27.3	4900	7500	0.053	51203
20	35	10	14.2	24.7	5100	7900	0.04	51104
	40	14	22.3	37.7	3900	6000	0.082	51204
25	42	11	19.5	37.2	4400	6800	0.059	51105
	47	15	27.8	50.4	3600	5500	0.012	51205
	52	18	35.7	61.4	3100	4800	0.018	51305
	60	24	55.6	89.4	2600	4000	0.34	51405
30	47	11	20.4	42.2	4300	6600	0.068	51106
	52	16	29.3	58.2	3400	5200	0.15	51206
	60	21	42.8	78.7	2700	4200	0.27	51306
	70	28	72.8	126	2200	3400	0.53	51406
35	52	12	20.4	44.7	3900	60000	0.09	51107
	62	18	39.2	78.2	2900	4500	0.22	51207
	68	24	55.5	105	2400	3700	0.39	51307
	80	32	87.1	155	1900	2900	0.79	51407
40	60	13	26.9	62.8	3400	5300	0.12	51108
	68	19	46.9	98.3	2700	4200	0.27	51208
	78	26	69.3	135	2100	3300	0.55	51308
	90	36	113	205	1700	2600	1.14	51408

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua  
Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com