



RODAMIENTOS AXIALES DE RODILLO

Dimensiones (mm)			Capacidad de Carga (N)		Velocidad Límite (rpm)	Peso (g)	Rodamiento
Dc1	Dc	Dw	Cr	Cor	Aceite	(gr)	
4	14	2	4380	7500	18000	0.7	AXK0414TN
5	15	2	4680	9100	17000	0.8	AXK0515TN
6	19	2	6740	15400	16000	1	AXK0619TN
8	21	2	7750	19000	15000	2	AXK0821TN
10	24	2	9150	24500	14000	3	AXK1024
12	26	2	9860	28600	13000	3	AXK1226
15	28	2	11200	35500	11000	4	AXK1528
17	30	2	11800	38600	10000	4	AXK1730
20	35	2	12900	45600	8500	5	AXK2035
25	42	2	13800	57800	7000	7	AXK2542
30	47	2	15600	69500	6000	8	AXK3047
35	52	2	16900	80100	5500	10	AXK3552
40	60	3	27500	113500	4700	16	AXK4060
45	65	3	29050	127600	4200	18	AXK4565
50	70	3	31500	13800	3900	20	AXK5070
55	78	3	37400	185000	3500	28	AXK5578
60	85	3	43900	232500	3200	33	AXK6085
65	90	3	45800	254600	3000	35	AXK6590
70	95	4	53600	254400	2900	60	AXK7095
75	100	4	54500	264600	2700	61	AXK75100
80	105	4	55600	278500	2600	63	AXK80105
85	110	4	57500	28800	2400	67	AXK85110
90	120	4	72500	401000	2300	86	AXK90120
100	135	4	90500	559500	2000	104	AXK100135
110	145	4	90500	617500	1900	122	AXK110145
120	155	4	101500	679600	1700	131	AXK120155

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua
 Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com