



### RODAMIENTOS DE AGUJA (B BH)

Dimensiones			Capacidad de Carga (lbf)		Velocidad Límite (rpm)		Peso lbs	Rodamiento
Fw	D	C	Dinámica	Estática	Grasa	Aceite		
.625 (5/8)	.8125(1 3/16)	.312(5/16)	1360	2080	3000	4500	0.014	B-105
	.8125(1 3/16)	.500(1/2)	2450	4430	3000	4500	0.022	B108
	.8125(1 3/16)	.625(5/8)	3110	6000	3000	4500	0.028	B-1010
	.8125(1 3/16)	.750(3/4)	3720	7570	3000	4500	0.034	B-1012
	.8745(-7/8)	.625(5/8)	3680	5680	4200	6500	0.039	BH-1010
	.8745(-7/8)	.750(3/4)	4450	7250	4200	6500	0.047	BH-1012
.750 (3/4)	1.0000	.375(3/8)	2180	3050	3600	5600	0.027	B-126
	1.0000	.500(1/2)	3170	4940	3600	5600	0.036	B-128
	1.0000	.625(5/8)	4080	6820	3600	5600	0.045	B-1210
	1.0000	.750(3/4)	4930	8710	3600	5600	0.054	B-1212
.875 (7/8)	1.1250(1 1/8)	.500(1/2)	3450	5760	3100	4800	0.042	B-148
	1.1250(1 1/8)	.750(3/4)	5370	10200	3100	4800	0.062	B-1412
	1.1250(1 1/8)	1.000	7100	14600	3100	4800	0.083	B-1416
1.000	1.250(1 1/4)	.375(3/8)	2500	4070	2800	4300	0.035	B-166
	1.250(1 1/4)	.500(1/2)	3710	6590	2800	4300	0.047	B-168
	1.250(1 1/4)	.625(5/8)	4770	9110	2800	4300	0.058	B-1610
	1.250(1 1/4)	.750(3/4)	5770	11600	2800	4300	0.070	B-1612
	1.250(1 1/4)	1.000	7630	16700	2800	4300	0.094	B-1616
	1.3125(1 5/16)	.625(5/8)	4950	8280	3400	5200	0.075	BH-1610
	1.3125(1 5/16)	.750(3/4)	6090	10800	3400	5200	0.090	BH-1612
1.250 (1 1/4)	1.5000(1 1/2)	.500(1/2)	4170	8240	2300	3500	0.057	B-208
	1.5000(1 1/2)	.625(5/8)	5370	11400	2300	3500	0.071	B-2010
	1.5000(1 1/2)	.750(3/4)	6490	14500	2300	3500	0.086	B-2012
	1.5000(1 1/2)	1.000	8590	20800	2300	3500	0.114	B-2016
	1.6250(1 5/8)	.500(1/2)	4420	6750	3300	5000	0.090	BH-208
	1.6250(1 5/8)	.750(3/4)	7440	13200	3300	5000	0.135	BH-2012
	1.6250(1 5/8)	1.000	10100	19500	3300	5000	0.179	BH-2016
1.3125 (1 5/16)	1.6250(1 5/8)	.625(5/8)	5740	10900	2600	4100	0.095	B-2110
1.3750 (1 3/8)	1.6250(1 5/8)	.750(3/4)	6830	16000	2100	3200	0.094	B-2212
	1.6250(1 5/8)	1.000	9030	22900	2100	3200	0.125	B-2216
	1.6250(1 5/8)	1.25(1 1/4)	11100	29900	2100	3200	0.156	B-2220
	1.7500(1 3/4)	.750(3/4)	7930	14500	3000	4700	0.146	BH-2212
	1.7500(1 3/4)	1.000	10700	21300	3000	4700	0.195	BH-2216
	1.7500(1 3/4)	1.25(1 1/4)	13400	28300	3000	4700	0.244	BH-2220
1.500 (1 1/2)	1.8750(1 7/8)	.750(3/4)	8290	15900	2800	4300	0.158	B-2412
	1.8750(1 7/8)	1.000	11200	23300	2800	4300	0.211	B-2416
	1.8750(1 7/8)	1.25(1 1/4)	13900	31000	2800	4300	0.263	B-2420

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua

Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com

