



### RODAMIENTOS DE AGUJA (SEGUIDORES DE LEVA KR)

Dimensiones (mm)							Torque Tuerca MA Nm	Capacidad de Carga Kgf		Velocidad Limite (grasa) rpm	Peso (g)	Rodamiento
D	d	C	B	B1	G	G1		Dinamica	Estatica			
16	6	11	28	16	M6X1	8	2.5	370	400	12000	18	KR16PP
19	8	11	32	20	M8X1.25	10	6.8	430	630	9000	28	KR19PP
22	10	12	36	23	M10X1.25	12	12.5	550	670	7000	42	KR22PP
26	10	12	36	23	M10X1.25	12	12.5	550	670	7000	58	KR26PP
30	12	14	40	25	M12X1.5	13	18.2	810	900	5500	87	KR30PP
32	12	14	40	25	M12X1.5	13	18.2	810	900	5500	105	KR32PP
35	16	18	52	32.5	M16X1.5	17	45.8	1230	1560	3600	169	KR35PP
40	18	20	58	36.5	M18X1.5	19	68.7	1500	2500	2900	250	KR40PP
47	20	24	66	40.5	M20X1.5	21	101	2110	3140	2400	386	KR47PP
52	20	29	66	40.5	M20X1.5	21	101	2110	3140	2400	461	KR52PP
62	24	29	80	49.5	M24X1.5	25	205	3110	3840	1900	815	KR62PP
72	24	29	80	49.5	M24X1.5	25	205	3110	3840	1900	1140	KR72PP

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua  
 Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com