



CHUMACERAS , REPUESTOS (UC)

Código	Diámetro Eje		Dimensiones (mm)								Capacidad de Carga (N)		Peso (kg)	
	Pulg	mm	D	B	C	S	S1	G	h	ds	Dinámica	Estática		
UC202		15	40	27.4	14	11.5	15.9	4.5	3.5	M5X0.8	9550	4780	0.12	
UC202-10	5/8												0.12	
UC203		17											0.11	
UC203-11	11/16												0.11	
UC204-12	3/4	20	47	31	16	12.7	18.3	4.7	4.4	M6X1	12800	6650	0.18	
UC204														0.17
UC205-14	7/8	25	52	34	17	14.3	19.7	5.5	4.3	M6X1	14000	7880	0.23	
UC205-15	15/16													0.22
UC205														0.21
UC205-16	1													0.2
UC206-18	1-1/8	30	62	38.1	19	15.9	22.2	5.5	5	M6X1	19500	11200	0.34	
UC206														0.32
UC206-19	1-3/16													0.31
UC206-20	1-1/4													0.3
UC207-20	1-1/4	35	72	42.9	20	17.5	25.4	6.5	5.8	M8X1	25700	15200	0.53	
UC207-21	1-5/16													0.51
UC207-22	1-3/8													0.48
UC207														0.47
UC207-23	1-7/16	40	80	49.2	21	19	30.2	8	6.3	M8X1	29600	18200	0.46	
UC208-24	1-1/2													0.68
UC208-25	1-9/16													0.65
UC208														0.64
UC209-26	1-5/8	45	85	49.2	22	19	30.2	8	6.8	M8X1	31850	20800	0.7	
UC209-27	1-11/16													0.74
UC209-28	1-3/4													0.7
UC209														0.68
UC210-30	1-7/8	50	90	51.6	23	19	32.6	9	6.5	M10X1 .25	35100	23200	0.87	
UC210-31	1-15/16													0.82
UC210														0.8
UC210-32	2													0.78

Av. La Industria, galpón 22, sector La Providencia c/c Av. Intercomunal, Turmero - Maracay, Maracay- Edo. Aragua
 Teléfonos: (0243) 269.43.49 / 269.44.80 / 269.00.34 / 269.09.93 / 269.15.32 / Fax: (0243) 269.38.49 / e-mail: maracay@bearings-and-seals.com